

# Functions

Name	Parameters	Description
fetchProgramInputs	- programId: <b>string</b> - callback: <b>function</b> => callback returning the inputs	Return the current PYTHON programs inputs
refreshView	- selectedViewContainerMeta: <b>ViewMetaData</b> Object - findEntityFn: <b>Function</b> - callback: <b>Function</b>	Update the current view with new MetaData
loadRegion	- regionId: <b>string</b>	Load specific region in the viewer
loadRegionData	- regionData: <b>interface</b> => { mode: <b>number</b> (0: None, 1: default type), points: [], pointsWorld: [], minY: <b>number</b> (Float), maxY: <b>number</b> (Float), minWorldZ: <b>number</b> (Float), maxWorldZ: <b>number</b> (Float) }	Load specific region data in the viewer
hideRegion	None	Hide the current loaded region
raycastViewPrimitives	- clientX: <b>number</b> - clientY: <b>number</b>	Ray-cast across all layers primitives in the view
requestFeatureInfo	- featureInfoQueryId: <b>number</b> - cellId: <b>number</b> - layerId: <b>number</b> - worldPoint: <b>[3]</b> - attributes: <b>[]</b> - customAttributes: <b>[]</b> - onComplete: <b>function</b> => callback on complete	Requests feature info to the content server for a given a voxel layer
zoomToExtents	None	Zooms the scene to the camera's extents

zoomToRegion	- regionData: <code>interface =&gt; {</code> mode: <code>number</code> (0: None, 1: default type), points: <code>[]</code> , pointsWorld: <code>[]</code> , minY: <code>number (Float)</code> , maxY: <code>number (Float)</code> , minWorldZ: <code>number (Float)</code> , maxWorldZ: <code>number (Float)</code> <code>}</code>	Zooms the region to the camera's extents
zoomIn	None	Zoom in the focus of the camera
zoomOut	None	Zoom out the focus of the camera
captureFrame	None	Capture a frame
frameWorldBounds	- worldBounds: <code>[3]</code>	Zoom a given bounds to the camera's extents
getCameraWorldPosition	None	Return the camera position in world coordinates
getWorldSceneBounds	None	Return the scene bounds in world coordinates
getOrthographicScale	None	Return the orthographic scale of the viewer
getDefaultGradientImage	- gradientId: <code>string</code>	Return the default gradient image used in the view
getCameraViewerPosition	None	Return the current position of the camera
getCameraWorldPosition	None	Return the current world position of the camera
getCameraAzimuthPlunge	None	Return the current camera azimuth plunge
getFocusViewerPosition	None	Return the current focus position of the viewer
getViewerProjection	None	Return the current viewer projection as a string
setOrthographicProjection	- enable: <code>Boolean</code>	Enable/disable orthographic projection
setUserSettings	- UserSettings: <code>interface =&gt; {</code> fontSize: <code>number</code> <code>}</code>	Sets user settings for the viewer, such as font size for all labels
setLabelVisibility	- showLabels: <code>Boolean</code>	Set visibility for all labels

setVisibility	<ul style="list-style-type: none"> <li>- layerId: <b>string</b></li> <li>- enable: <b>Boolean</b></li> </ul>	Enable or disable visibility for a given meta component
setTransparency	<ul style="list-style-type: none"> <li>- layerId: <b>string</b></li> <li>- opacity: <b>number (Float)</b></li> </ul>	Set opacity for a given meta component
setDiffuseTransparency	<ul style="list-style-type: none"> <li>- layerId: <b>string</b></li> <li>- diffuseOpacity: <b>number (Float)</b></li> </ul>	Set diffuse map opacity for a given meta component
setDiffuseBlendMode	<ul style="list-style-type: none"> <li>- layerId: <b>string</b></li> <li>- diffuseBlendMode: <b>number (Float)</b></li> </ul>	Set diffuse blend mode for a given meta component
setDrillholeSettings	<ul style="list-style-type: none"> <li>- layerId: <b>string</b></li> <li>- drillholesSettings: <b>interface =&gt; {</b>  showRoots: <b>Boolean</b>,  showRootLabels: <b>Boolean</b>,  showLines: <b>Boolean</b>,  showTubes: <b>Boolean</b>,  showColorAttributeLabels: <b>Boolean</b>,  attributesTextSize: <b>number</b>,  leftColorAttributeIndices: <b>number[]</b>,  rightColorAttributeIndices: <b>number[]</b>,  colorAttributeRawData: <b>string</b>  <b>}</b></li> </ul>	Set drill hole settings for a given meta vector component, such as collar visibility, collar label id visibility, holes rendered as lines or tubes, holes attribute label filter

<p>setGeoChemSettings</p>	<pre> - layerId: string - geoCheomSettings: interface =&gt; {   showPolygon: Boolean,   showInside: Boolean,   polygonPoints: interface =&gt; {     vfPoints: number[3],     wPoints: number[3]   },   showZ: Boolean,   geoShowLabels: Boolean,   geoLabelSize: number,   geoShowElevation: Boolean,   planeValue: number,   attributes: interface =&gt; {     top: {       attribute: string,       color: [3],       index: number     },     bottom: {       attribute: string,       color: [3],       index: number     }   },   left: {     attribute: string,     color: [3],     index: number   }   right: {     attribute: string,     color: [3],     index: number   }   },   geoSize: number,   geoShape: number,   } </pre>	<p>Set Geo chem settings for a given meta vector component, such as attribute label visibility, attribute label color, size and shape</p>
<p>setAttributeQuery</p>	<pre> - layerId: string - attributeQuery: interface =&gt; {   type: number,   attributeQueryBuilderValue: string,   builderAttributeFilters: [],   builderAttributeRawData: string   } </pre>	<p>Sets attribute query for a given meta component</p>

<p>setLabelQuery</p>	<pre>- layerId: string  - labelQuery: interface =&gt; {   type: number,   builderLabelFilters: [],   builderLabelRawData: string,   showPolygon: Boolean,   showInside: Boolean,   polygonPoints: interface =&gt; {     vfPoints: number[3],     wPoints: number[3]   } }</pre>	<p>Sets label query for a given meta component</p>
<p>setBlockModelLimits</p>	<pre>- layerId: string - BlockModelLimits: interface =&gt; {   indexFilter: number,   regionType: 0,   bounds: interface =&gt; {     min: {       x: number (Float),       y: number (Float),       z: number (Float),     },     max: {       x: number (Float),       y: number (Float),       z: number (Float),     }   },   enable: {     x: Boolean,     y: Boolean,     z: Boolean   }, }</pre>	<p>Sets block model limits for a given meta block tree component</p>

setColorLegend	<ul style="list-style-type: none"> <li>- layerId: <b>string</b></li> <li>- colorLegend: <b>interface</b> =&gt; { <ul style="list-style-type: none"> <li>type: <b>number</b> (1: Static Color, 2: Data Driven),</li> <li>dataDrivenColorAttribute: <b>string</b>,</li> <li>dataDrivenColorAttributeIndex: <b>number</b>,</li> <li>dataDrivenColorMinValue: <b>number</b> (Float),</li> <li>dataDrivenColorMaxValue: <b>number</b> (Float),</li> <li>dataDrivenColorStepSize: <b>number</b> (Float),</li> <li>dataDrivenUseAttributeGradient: <b>Boolean</b>,</li> <li>dataDrivenAttributeGradient: <b>[]</b>,</li> <li>staticColorDoubleSided: <b>Boolean</b>,</li> <li>staticColorFrontSideRGB: <b>[3]</b>,</li> <li>staticColorBackSideRGB: <b>[3]</b>,</li> <li>gradientId: <b>string</b>,</li> <li>dataDrivenColorDistribution: <b>[]</b></li> </ul> </li> </ul>	Sets color legend for a given meta component
setCollarLegend	<ul style="list-style-type: none"> <li>- layerId: <b>string</b></li> <li>- collarLegend: <b>interface</b> =&gt; { <ul style="list-style-type: none"> <li>type: <b>number</b>, (1: default type)</li> <li>staticColor: <b>[3]</b>,</li> <li>staticRadius: <b>number</b>,</li> <li>textSize: <b>number</b>,</li> </ul> </li> </ul>	Sets collar legend for a given meta vector component
setFatLineThickness	<ul style="list-style-type: none"> <li>- layerId: <b>string</b></li> <li>- FlatlineThickness: <b>number</b></li> </ul>	Sets fat line thickness for a given meta vector component
setTubeDiameterLegend	<ul style="list-style-type: none"> <li>- layerId: <b>string</b></li> <li>- tubeDiameterLegend: <b>interface</b> =&gt; { <ul style="list-style-type: none"> <li>scaleMode: <b>number</b>,</li> <li>cylinderRadius: <b>number</b> (Float),</li> <li>attribute: <b>string</b>,</li> <li>attributeIndex: <b>number</b>,</li> <li>rangeMin: <b>number</b> (Float),</li> <li>rangeMax: <b>number</b> (Float),</li> <li>rangeStep: <b>number</b> (Float),</li> <li>radiusMin: <b>number</b> (Float),</li> <li>radiusMax: <b>number</b> (Float)</li> </ul> </li> </ul>	Sets tube diameter legend for a given meta vector component
setTraceSettings	<ul style="list-style-type: none"> <li>- layerId: <b>string</b></li> <li>- traceSettings: <b>interface</b> =&gt; { <ul style="list-style-type: none"> <li>traceThickness: <b>number</b> (Float)</li> </ul> </li> </ul>	Sets fat line thickness for a given meta vector component using trace settings

setMeshPropertiesAt	<ul style="list-style-type: none"> <li>- layerId: <b>string</b></li> <li>- meshIndex: <b>number</b></li> <li>- meshVisible: <b>Boolean</b></li> <li>- meshOpacity: <b>number (Float)</b></li> <li>- meshUseParentColorLegend: <b>Boolean</b></li> <li>- meshStaticColor: <b>[3]</b>,</li> </ul>	Sets mesh properties at a specific mesh index for a given meta surface component
setMeshProperties	<ul style="list-style-type: none"> <li>- layerId: <b>string</b></li> <li>- meshProperties: <b>interface =&gt; {</b></li> <li style="padding-left: 20px;">parentLayer: <b>string</b>,</li> <li style="padding-left: 20px;">meshIndex: <b>number</b>,</li> <li style="padding-left: 20px;">meshVisible: <b>Boolean</b>,</li> <li style="padding-left: 20px;">meshOpacity: <b>number (Float)</b>,</li> <li style="padding-left: 20px;">meshUseParentColorLegend: <b>Boolean</b>,</li> <li style="padding-left: 20px;">meshStaticColor: <b>[3]</b>,</li> <li style="padding-left: 20px;">meshStaticBackColor: <b>[3]</b></li> <li><b>}</b></li> </ul>	Sets mesh properties for all meshes for a given meta surface component
setImageProperties	<ul style="list-style-type: none"> <li>- layerId: <b>string</b></li> <li>- imageProperties: <b>interface =&gt; {</b></li> <li style="padding-left: 20px;">visible: <b>Boolean</b>,</li> <li style="padding-left: 20px;">transparency: <b>number (Float)</b>,</li> <li style="padding-left: 20px;">contrast: <b>number (Float)</b>,</li> <li style="padding-left: 20px;">brightness: <b>number (Float)</b>,</li> <li style="padding-left: 20px;">gamma: <b>number (Float)</b>,</li> <li style="padding-left: 20px;">blendMode: <b>number</b>,</li> <li style="padding-left: 20px;">blendMakeColorTransparent: <b>Boolean</b>,</li> <li style="padding-left: 20px;">blendInvertSelection: <b>Boolean</b>,</li> <li style="padding-left: 20px;">blendTransparentColor: <b>[3]</b>,</li> <li style="padding-left: 20px;">blendSelectionTolerance: <b>number (Float)</b>,</li> <li style="padding-left: 20px;">blendOutputTransparency: <b>number (Float)</b>,</li> <li style="padding-left: 20px;">blendOutputColor: <b>[3]</b>,</li> <li style="padding-left: 20px;">bands: <b>[4]</b></li> <li><b>}</b></li> </ul>	Sets image properties for a given meta block tree/surface/vector component

setImagePropertiesAt	<ul style="list-style-type: none"> <li>- layerId: <b>string</b></li> <li>- imageId: <b>string</b></li> <li>- imageVisible: <b>Boolean</b></li> <li>- imageOpacity: <b>number (Float)</b></li> <li>- imageContrast: <b>number (Float)</b></li> <li>- imageBrightness: <b>number (Float)</b></li> <li>- imageGamma: <b>number (Float)</b></li> <li>- imageBlendMode: <b>number</b></li> <li>- imageBlendMakeColorTransparent: <b>Boolean</b></li> <li>- imageBlendTransparentColor: <b>[3]</b></li> <li>- imageBlendSelectionTolerance: <b>number (Float)</b></li> <li>- imageBlendOutputColor: <b>[3]</b>,</li> <li>- imageBlendInvertSelection: <b>Boolean</b></li> <li>- imageBands: <b>[3]</b></li> </ul>	Sets the image properties at a specific image index for a given meta block tree/surface/vector component
setNavigationMode	<ul style="list-style-type: none"> <li>- mode: <b>number</b></li> </ul>	<p>Set the navigation mode of the camera</p> <ul style="list-style-type: none"> <li>- mode = 0 =&gt; use rotation as primary mouse input</li> <li>mode = 1 =&gt; use pane as primary mouse input</li> </ul>
setViewMetaData	<ul style="list-style-type: none"> <li>- compositedMeta: <b>ViewMetaData Object</b></li> </ul>	
setExtendedMeta	<ul style="list-style-type: none"> <li>- index: <b>number</b></li> <li>- extendedMeta: <b>JSON Object</b></li> <li>- viewId: <b>number (optional)</b></li> </ul>	<p>Set extended meta to the current meta data Object</p> <p>Note: The ViewId is optional parameter by default it has a value of 0 to indicate first view</p>
applyZoomDelta	<ul style="list-style-type: none"> <li>- deltaDistance: <b>number</b></li> </ul>	Apply a zoom given a delta value
enableCrossSectionFading	<ul style="list-style-type: none"> <li>- enableFading: <b>Boolean</b></li> </ul>	Enable or Disables Cross Section Fading
alignCameraToDirection	<ul style="list-style-type: none"> <li>- direction: <b>number</b></li> </ul>	Align the camera forward to the given direction
startSegment	<ul style="list-style-type: none"> <li>- segmentType: <b>number</b></li> <li>- keepSegmentAlive: <b>Boolean</b></li> <li>- onCompleteSegment: <b>function =&gt;</b> callback on complete of the segment</li> <li>- onCancelSegment: <b>function =&gt;</b> callback on canceling of the segment</li> </ul>	Start a segment procedure

stopSegment	- segmentId: <b>number</b>	Stop a segment procedure
startOrthoPoly	- orthoPolyType: <b>number</b> - keepOrthoPolyAlive: <b>Boolean</b> - onCompleteOrthoPoly: <b>function</b> => callback on complete of the Ortho poly - onCancelOrthoPoly: <b>function</b> => callback on cancel of the Ortho poly	Start an orthographic segment list procedure
stopOrthoPoly	- orthoPolyId: <b>number</b>	Stop an orthographic segment list procedure
createDot	- dotId: <b>number</b> - worldPoint: <b>[3]</b>	Create a dot in the scene
destroyDot	- dotId: <b>number</b>	Destroy an existing dot
createViewMetaData	None	Create ViewMetaData Object
addViewer	- projectId: <b>string</b> - viewId: <b>string</b> - layers: <b>Array</b> - findEntityFn: <b>function</b> => callback to find the entity from within the caller of the function - isBaseMap: <b>Boolean</b> - currentProject: <b>JSON Object</b>	Add viewer to the multiCRS Viewer pool
viewerExists	- layer: <b>JSON Object</b>	Check if a layer has a viewer associated with it.
setViewerProjection	- projectId: <b>string</b> - entityId: <b>string</b>	Set the current projection of the view based on the selected entity passed to the function as the second parameter
updateCrossSectionEnableHighlight	- enableHighlight: <b>Boolean</b>	Update the cross section to enable/disable highlight

<p>updateCrossSectionPresetType</p>	<p>- presetType: number</p> <p>0 : No Clipping; Hide +X +Y +Z +W</p> <p>1 : Clip Outside; Show +X +Y +Z; Hide +W</p> <p>2 : Clip Outside; Show +Z; Hide +X +Y +W</p> <p>3 : Clip Outside; Show +X; Hide +Y +Z +W</p> <p>4 : Clip Outside; Show +Y; Hide +X +Z +W</p> <p>5 : Clip Normal; Show +Z; Hide +X +Y +W</p> <p>6 : Clip Normal; Show -X; Hide +Y +Z +W</p> <p>7 : Clip Normal; Show -Y; Hide +X +Z +W</p> <p>8 : Clip Normal; Show -Z; Hide +X +Y +W</p> <p>9 : Clip Normal; Show +X; Hide +Y +Z +W</p> <p>10 : Clip Normal; Show +Y; Hide +X +Z +W</p> <p>11 : Clip Normal; Show +W; Hide +X +Y +Z</p> <p>12 : Clip Normal; Show -W; Hide +X +Y +Z</p> <p>13 : Clip Outside; Show +W; Hide +X +Y +Z</p>	<p>Control the Cross section of the view by presets</p>
-------------------------------------	--	---

Revision #3

Created 17 March 2025 19:49:03 by admin

Updated 17 March 2025 20:09:41 by admin